




## OKS 270 - Product Information

### Fields of Application:

Lubrication of dirt-sensitive sliding points in mechanisms in precision mechanics, paper and textile-processing machines, in filling, labelling and packaging machines of the pharmaceutical and food processing industries, on electrical and household appliances, office machines etc. Assembly lubrication with large lubricant reservoir, e.g. chucks in which a supplemental relubrication at longer intervals with grease guns is possible.

### OKS 270 White Grease Paste



### Advantages and Benefits:

Excellent suited for dirt-free assembly and long-term lubrication. Highly effective due to optimum solid lubricant combination. Broad range of uses in area of parts sensitive to soiling. Low consumption due to formation of highly effective lubricating films. Good corrosion protection behaviour.

### Application:

For best adhesion, clean contamination and other lubricants from thread and slide surfaces. Best way is to clean mechanically first (for example, with a wire brush) and then with OKS 2610 / OKS 2611 universal cleaning agent. Use a brush, spatula or similar to apply evenly a suitable quantity of paste to the head or nut contact surface and to the thread. The paste will also act as a sealant. Do not use paste instead of grease and mix only with suitable lubricants. Our customer advice service will be pleased to help should you have any further questions.

### Additional Information:

#### Liefergebände:

- 250 g Tin
- 1 kg Tin
- 5 kg Hobbock
- 25 kg Hobbock

#### Version:

E-01.1/17

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark



# OKS 270 White Grease Paste

## Technical Data

	Norm	Conditions	Unit	Value
<b>Base Oil</b>				
Type				White oil
Viscosity	DIN 51562-1	40°C	mm <sup>2</sup> /s	100
Flash point	DIN ISO 2592	> 79	°C	> 210
<b>Thickener</b>				
Type				Lithiumhydroxystearate
Unworked penetration	DIN ISO 2137	no shear stress	0,1 mm	280 - 310
Drop point	DIN ISO 2176		°C	> 190
<b>Additives</b>				
Solid lubricants, type				white solid lubricants, PTFE
<b>Application Data</b>				
Density	DIN EN ISO 3838	20°C	g/cm <sup>3</sup>	1,15
Colour				light-coloured
<b>Service Temperatures</b>				
Minimum service temperature			°C	-25
Maximum service temperature			°C	125
Water resistance	DIN 51 807-1	90°C	Grade 0-3	0
<b>Wear Protection Tests</b>				
VBT- weld load (Four ball test rig)	DIN 51 350-4		N	5.000
<b>Friction Values</b>				
Press-Fit-Test	E DIN 51 833		μ	0,14, chatterfree
Thread friction value	DIN EN ISO 16047	Screw: ISO 4017 M10x55-8.8 plain Nut: ISO 4032 M10-10 plain	μ	0,09

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark